

Enduroflex Sopradere Quick

SOPRADERE QUICK is a ready-to-use cold applied fast drying bitumen emulsion primer composed of bitumen, volatile solvents and adhesive additives.

User application

SOPRADERE QUICK is used as cold-applied primer on concrete, degreased metal or wood-based substrate, to increase the adhesion of bituminous waterproofing membranes hot bonded or torched-on, in compliance with French Code of Practice DTU 43 (NF P 84-204).

Composition

	SOPRADERE QUICK
Physical state	Dark homogeneous liquid, leaving a black coloured film after drying
Dry content	> 40 % of weight
Density at 20°C	about 950 kg/m ³ (± 50)
Viscosity cup n°4 at 20°C	23 to 27 °C
Flash point (ASTM D 56)	+ 24°C
Drying time on concrete	Less than 30 minutes

Packaging

	SOPRADERE QUICK
Packaging	Cans of 5 or 25 litres
Consumption	<p>Consumption depends on the uses and the substrate. On rough and absorbent substrate (i.e concrete, wood) :</p> <ul style="list-style-type: none"> - 5 L can cover about 20 m² - 25 L can cover about 100 m² <p>On smooth, non absorbent substrate (i.e metal), the average consumption may be lower.</p>
Storage	The product can be stored until 12 months at a temperature between 5°C and 35°C in closed original packaging and protected from the sun.

Installation

Before use, well homogenize **SOPRADERE QUICK**. The tools used (roll, brush, rubber squeegee) must be clean.

SOPRADERE QUICK must be applied with a brush or a roller onto dry, clean surfaces, free of all dust and non-adhesive parts (concrete, wood, metal ... previously degreased).

Let dry completely before apply the waterproofing membrane.

Cleaning tools:

Petroleum solvent (white spirit, xylene for example).

Special indications

Hygiene, health and environment:

- Flammable: keep away from flames and sparks during use.
- **SOPRADERE QUICK** contains xylene.
- Ensure that all cans, empty or full, containing flammable substances are kept at least 10 m away.
- If spray gun is used, ensure that no incompatible material is used that may create sparks.
- Close cans properly after each use.
- Do not breathe in fumes.
- Avoid the product coming in contact with eyes.
- Do not smoke while product is being used.
- Do not swallow.
- Do not throw wastes into sewers.

For further information, please refer to relevant Safety Data Sheet.