

## Enduroflex Rubber Pads

### DESCRIPTION:

**Enduroflex Rubber Pads** are manufactured from recycled rubber granules and are available in a variety of thicknesses and sizes.

Rubber Pads prevent damage to roofs and allow drainage beneath the rooftop flooring. They can also smooth out any unevenness on the roof as they are available in different thicknesses.

Rubber Pads can be used under concrete tiles, stone, wood, plastic, wood composite and for placing beneath aluminium support structures for solar panels.

### BENEFITS:

- Protection of existing roof;
- Can be placed directly on roofing (except PVC roofing);
- Spacing to allow drainage;
- Easy to fit;
- Frost resistant;
- Recyclable.

### SPECIFICATIONS:

- Colour: black;
- Dimensions: 100 mm x 100 mm, 150 mm x 150 mm, 200 mm x 200 mm;
- Thickness: 10 mm;
- Maximum load per pad:(with full support) 100 mm x 100 mm – 150 kg;  
150 mm x 150 mm – 337,5 kg;  
200 mm x 200 mm – 600 kg.

### PACKAGING:

- 100 x 100 x 10 mm: 150 pc/box 36 boxes/palet;
- 150 x 150 x 10 mm: 120 pc/box 24 boxes/palet;
- 200 x 200 x 10 mm: 80 pc/box 25 boxes/palet.



Edition : 07-July-21